



polk



LEGEND SERIES

■ L800

Three Way SDA-PRO Floorstanding Loudspeaker

Frequency	: 32 Hz-38 kHz (± 3 dB)
Power Handling	: 25-300W
Sensitivity	: 87dB SPL@2.83V
Impedance	: 4 ohms (2.8 min.)
Driver Size	: 1" Ring Radiator (x2) HF, 2 x 5.25" (x2) MF, 10" (x2) LF
Dimensions	: 455.6 x 1234.5 x 441.4 mm
Weight	: 53.5kg (118 lbs)

IMAX
ENHANCED
CERTIFIED



■ L600

Three Way Floorstanding Loudspeaker

Frequency	: 34 Hz-38 kHz (± 3 dB)
Power Handling	: 20-300W
Sensitivity	: 86dB SPL@2.83V
Impedance	: 4 ohms (3.3 min.)
Driver Size	: 1" Ring Radiator HF, 5.25" MF, 7" (x2) LF
Dimensions	: 329.3 x 1185.9 x 404 mm
Weight	: 35.3kg (77.8 lbs)

IMAX
ENHANCED
CERTIFIED



■ L400

Three Way Centre Channel

Frequency	: 55 Hz-38 kHz (± 3 dB)
Power Handling	: 25-300W
Sensitivity	: 87.5dB SPL@2.83V
Impedance	: 4 ohms (3.4 min.)
Driver Size	: 1" Ring Radiator HF, 4" MF, 6.5" (x2) LF
Dimensions	: 660.4 x 239.1 x 341.5 mm
Weight	: 18.5kg (40.8 lbs)



■ L200

Two Way Bookshelf Speaker

Frequency	: 46 Hz-38 kHz (± 3 dB)
Power Handling	: 30-200W
Sensitivity	: 85.5dB SPL@2.83V
Impedance	: 4 ohms (3.4 min.)
Driver Size	: 1" Ring Radiator HF, 6.5" MF
Dimensions	: 211.5 x 397.9 x 337.8 mm
Weight	: 10kg (22 lbs)

IMAX
ENHANCED
CERTIFIED



■ L100

Two Way Bookshelf Speaker

Frequency	: 57 Hz-38 kHz (± 3 dB)
Power Handling	: 30-160 W
Sensitivity	: 85.5 dB SPL@2.83 V
Impedance	: 4 ohms (3 min.)
Driver Size	: 1" Ring Radiator HF, 5.25" MF
Dimensions	: 197.5 x 346.4 x 286.8 mm
Weight	: 7.65 kg (16.9 lbs)

IMAX
ENHANCED
CERTIFIED



■ L900

Two Way Height Module for Atmos

Frequency	: 150 Hz-30 kHz (± 3 dB)
Power Handling	: 30-100 W
Sensitivity	: 86dB SPL@2.83 V
Impedance	: 4 ohms (2.8 min.)
Driver Size	: 0.75" Ring Radiator HF, 4" MF
Dimensions	: 178 x 250 x 83.9 mm
Weight	: 1.5 kg (3.3 lbs)

IMAX
ENHANCED
CERTIFIED





RESERVE SERIES

■ R700

Premium Floorstanding Loudspeaker

Frequency Response	: 38 Hz-37 kHz (±3dB)
Power	: 50-300W
Sensitivity	: 88db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / 6 1/2" Turbine Cone / Two 8" Polypropylene
Dimensions (WxHxD)	: 12.6 x 45 x 16.9 in
Weight	: 79.1 lbs/35.9 kg

IMAX
ENHANCED
CERTIFIED



■ R600

Floorstanding Loudspeake

Frequency Response	: 43 Hz-38 kHz (±3dB)
Power	: 25-200W
Sensitivity	: 87.5db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / Two 6 1/2" Turbine Cone
Dimensions (WxHxD)	: 11 x 41.9 x 15 in
Weight	: 47.3 lbs/21.5

IMAX
ENHANCED
CERTIFIED



■ R500

Compact Floorstanding Loudspeaker

Frequency Response	: 49 Hz-36 kHz (±3dB)
Power	: 25-200W
Sensitivity	: 87db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / Two 5 1/4" Turbine Cone
Dimensions (WxHxD)	: 10.1 x 41.1 x 13.7 in
Weight	: 39 lbs/17.7 kg

IMAX
ENHANCED
CERTIFIED



■ R400C

Large Center Channel Speaker

Frequency Response	: 48 Hz-39 kHz (± 3 dB)
Power	: 20-200W
Sensitivity	: 89db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / Two 6 1/2" Turbine Cone
Dimensions (WxHxD)	: 24.2 x 7.8 x 13.8 in
Weight	: 32.8 lbs/14.9 kg



■ R350C

Slim Center Channel Speaker (L/C/R)

Frequency Response	: 75 Hz-35 kHz (± 3 dB)
Power	: 25-200W
Sensitivity	: 87db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / Four 4" Turbine Cone
Dimensions (WxHxD)	: 30 x 5.5 x 7.4 in
Weight	: 20 lbs/9 kg



■ R300C

Compact Center Channel Speaker

Frequency Response	: 65 Hz-38 kHz (± 3 dB)
Power	: 20-200W
Sensitivity	: 86.5db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / Two 5 1/4" Turbine Cone
Dimensions (WxHxD)	: 19 x 6.8 x 8.9 in
Weight	: 16.8 lbs/7.6 kg



■ R200

Large Bookshelf Speaker

Frequency Response	: 51 Hz-38 kHz (± 3 dB)
Power	: 30-200W
Sensitivity	: 86db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / 6 1/2" Turbine Cone
Dimensions (WxHxD)	: 7.5 x 14.1 x 13.9 in
Weight	: 19.1 lbs/8.7 kg



■ R100

Bookshelf Speaker

Frequency Response	: 58 Hz-39 kHz (± 3 dB)
Power	: 30-150W
Sensitivity	: 86db
Impedance	: 8 ohms
Driver Size	: 1" Pinnacle Ring Radiator / 5 1/4" Turbine Cone
Dimensions (WxHxD)	: 6.5 x 12.8 x 10.2 in
Weight	: 12.2 lbs/5.5 kg



■ R900HT

Atmos Height Module

Frequency Response	
Power	: 45-100W
Sensitivity	: 85.5dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 0.75" Pinnacle Ring Radiator Tweeter 4" Turbine Cone - Mid/Woofer
Dimensions	: 6.5 x 6.2 x 12.6 in
Weight (H X W X D)	: 6.6 lbs/3 kg





**SIGNATURE
ELITE
SERIES**

ES60

High-Resolution Hi-Fi Loudspeaker

Frequency Response	: 36 Hz-40 kHz
Power	: 20-300W
Sensitivity	: 90dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 1"/2.54cm Terylene High-Resolution Dome Tweeter (3) 6.5"/16.5cm low distortion mica- fortified poly propylene drivers
Dimensions (WxHxD)	: (W)8.5" x (H)44.5" x (D)15.7"
Weight	: 52lbs/23.6kg



ES55

High-Resolution Hi-Fi Loudspeaker

Frequency Response	: 40 Hz-40 kHz
Power	: 20-200W
Sensitivity	: 90dB
Impedance	: 8 ohms (3.3 min.)
Driver Size	: 1"/2.54cm Terylene High-Resolution Dome Tweeter (2) 6.5"/16.5cm low distortion mica- fortified poly propylene drivers
Dimensions (WxHxD)	: (W)8.5" x (H)41.5" x (D)12.5"
Weight	: 44lbs/20kg



■ ES50

High-Resolution Hi-Fi Loudspeaker

Frequency Response	:	42 Hz-40 kHz
Power	:	20-150W
Sensitivity	:	89dB
Impedance	:	8 ohms (3.3 min.)
Driver Size	:	1"/2.54cm Terylene High-Resolution Dome Tweeter (2) 5.25"/13.34cm low distortion mica- fortified polypropylene drivers
Dimensions (WxHxD)	:	(W)7.5" x (H)37.4" x (D)10.9"
Weight	:	32lbs/14.5kg



■ ES35

High-Resolution Hi-Fi Slim Centre Speaker

Frequency Response	:	70 Hz-40 kHz
Power	:	20-150W
Sensitivity	:	88dB
Impedance	:	8 ohms (3.4 min.)
Driver Size	:	1"/2.54cm Terylene dome tweeter (6) 3"/7.62cm low distortion mica-fortified polypropylene drivers
Dimensions (WxHxD)	:	(W)24.4" x (H)4.1" x (D)6.1"
Weight	:	14lbs / 6.4kg



■ ES30

High-Resolution Hi-Fi Centre Speaker

Frequency Response	:	55 Hz-40 kHz
Power	:	20-150W
Sensitivity	:	89dB
Impedance	:	8 ohms (3 min.)
Driver Size	:	1"/2.54cm Terylene dome tweeter (2) 5.25"/13.34cm low distortion mica-fortified polypropylene drivers
Dimensions (WxHxD)	:	(W)20" x (H)7.5" x (D)10.6"
Weight	:	19lbs/8.6kg



■ ES20

High-Resolution Hi-Fi Bookshelf Speaker

Frequency Response	:	44 Hz-40 kHz
Power	:	20-150W
Sensitivity	:	88dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	1"/2.54cm high-resolution Terylene dome tweeter 6.5"/16.5cm low distortion mica- fortified polypropylene drivers
Dimensions (WxHxD)	:	(W)8.5" x (H)14.8" x (D)13.8"
Weight	:	17lbs/7.7kg



■ ES15

High-Resolution Hi-Fi Compact Bookshelf Speaker

Frequency Response	:	48 Hz-40 kHz
Power	:	20-100W
Sensitivity	:	88dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	1"/2.54cm high-resolution Terylene dome tweeter 5.25"/13.34 cm low distortion mica- fortified polypropylene drivers
Dimensions (WxHxD)	:	(W)7.5" x (H)12" x (D)10.2"
Weight	:	13lbs/5.9kg



■ ES10

High-Resolution Hi-Fi Satellite Bookshelf Speaker

Frequency Response	: 75 Hz-40 kHz
Power	: 20-100W
Sensitivity	: 87dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 1"/2.54cm high-resolution Terylene dome tweeter 4"/10.16cm low distortion mica-fortified polypro pylene drivers
Dimensions (WxHxD)	: (W)7.5" x (H)12" x (D)10.2"
Weight	: 6lbs/2.7kg



**MONITOR
SERIES**

■ Monitor XT70

High-Resolution Hi-Fi Loudspeaker

Frequency Response	: 35 Hz-40 kHz
Power	: 25-200W
Sensitivity	: 89dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 1" Terylene dome : (2) 6.5" Bi-laminate paper : (2) 8" passive radiators
Dimensions (WxHxD)	: 9.25" x 40.4" x 12.5"
Weight	: 35lbs/15.88kg



■ Monitor XT60

High-Resolution Hi-Fi Loudspeaker

Frequency Response	:	38 Hz-40 kHz
Power	:	25-200W
Sensitivity	:	86dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	1" Terylene dome
	:	6.5" Bi-laminate paper
	:	(2) 6.5" passive radiators
Dimensions (WxHxD)	:	7.5" x 36.4" x 9.09"
Weight	:	35lbs/15.88kg



■ Monitor XT35

High-Resolution Hi-Fi Slim Centre Speaker

Frequency Response	:	84 Hz-26 kHz
Power	:	25-200W
Sensitivity	:	87dB
Impedance	:	8 ohms (3.4 min.)
Driver Size	:	1" Terylene dome
	:	(4) 3" Bi-laminate paper
Dimensions (WxHxD)	:	24.4" x 4.15" x 5.55"
Weight	:	14lbs/6.4kg



■ Monitor XT30

High-Resolution Hi-Fi Centre Speaker

Frequency Response	:	55 Hz-40 kHz
Power	:	30-200W
Sensitivity	:	89dB
Impedance	:	8 ohms (3 min.)
Driver Size	:	1" Terylene dome
	:	(2) 5-1/4" Bi-laminate paper
Dimensions (WxHxD)	:	19.9" x 6.50" x 8.13"
Weight	:	13lbs/5.9kg



■ Monitor XT20

High-Resolution Hi-Fi Bookshelf Speaker

Frequency Response	:	38 Hz-40 kHz
Power	:	30-200W
Sensitivity	:	87dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	1" Terylene dome
	:	6.5" Bi-laminate paper
Dimensions (WxHxD)	:	7.5" x 18" x 10.99"
Weight	:	12lbs/5.44kg



■ Monitor XT15

High-Resolution Hi-Fi Compact Bookshelf Speaker

Frequency Response	:	48 Hz-40 kHz
Power	:	30-150W
Sensitivity	:	86dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	1" Terylene dome
	:	5.25" Bi-laminate paper
Dimensions (WxHxD)	:	6.5" x 10.6" x 7.18"
Weight	:	9lbs/4.08kg



■ Monitor XT15

High-Resolution Hi-Fi Compact Bookshelf Speaker

Frequency Response	: 48 Hz-40 kHz
Power	: 30-150W
Sensitivity	: 86dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 1" Terylene dome
	: 5.25" Bi-laminate paper
Dimensions (WxHxD)	: 6.5" x 10.6" x 7.18"
Weight	: 9lbs/4.08kg



■ Monitor XT90

Dolby Atmos Certified Height Speaker

Frequency Response	: 94 Hz-22 kHz
Power	: 30-100W
Sensitivity	: 89dB
Impedance	: 8 ohms (2.8 min.)
Driver Size	: 4" Bi-laminate paper
Dimensions (WxHxD)	: 7.5" x 5.64" x 8.38"
Weight	: 6lbs/2.72kg



FUSION T SERIES

T Series 5.0 Speaker Package

■ T50

Home Theatre Floor Standing Speaker

- High performance front speakers • 150W • 2-Way • 2 speakers floor stander

■ T30

Home Theatre Center Speaker

- High performance centre speaker • 100W • 2-Way • 3 speakers system

■ T15

Home Theatre Book Shelf Speaker

- High performance surround speaker • 150W • 2-Way • 2 speaker system





**BLACKSTONE
SERIES**

Premium 5.1 speaker packages from Polk Audio with dynamic "Powerport" technology for larger than life movie experiences.

TL1600

5.1 Satellite Home Theatre Speaker System

Frequency	: 40 Hz -22 kHz
System Power	: 600 W
Sensitivity	: 89 dB
Impedance	: 8 ohms
Powered Subwoofer	: 100 W
Driver Size	: Satellite : 63mm MF, 12.7 mm HF
	: Center: 2 x 63 mm MF, 12.7 mm HF
	: Subwoofer: 8 inch
Dimensions	: Satellite: 165 x 95 x 123 mm
	: Center: 103 x 380 x 89 mm
	: Subwoofer: 352 x 317 x 317 mm
Weight	: Satellite: 0.8 kg, Center: 1.5 kg, Subwoofer: 9.2 kg



POWERED SUBWOOFERS

■ DSW PRO 660

High Performance Subwoofer 500W, 12" Downward Firing Bass Reflex

Frequency	: 20 Hz-160 Hz
Crossover Frequency	: 60 Hz-120 Hz
Power Handling	: 500 W
Driver Size	: 12 inch
Dimensions	: 435 x 419 x 419 mm
Weight	: 20 kg



■ DSW PRO 550

High Performance Subwoofer 400W, 10" Downward Firing Bass Reflex

Frequency	: 23 Hz-160 Hz
Crossover Frequency	: Variable
Power Handling	: 400 W
Driver Size	: 10 inch
Dimensions	: 410 x 381 x 394 mm
Weight	: 18.6 kg



■ HTS 12

400W, 12" Front Firing Downward Ported Type

Frequency Response	: 30 Hz - 120 Hz (±3 dB)
Power	: 400 W
Driver Size	: 1 x 300 mm (12 in.)
Dimensions (HxWxD)	: 18.5" x 17.12" x 18.12"
Weight	: 22.63 kg



■ HTS 10

200W, 10" Front Firing Downward Ported Type

Frequency Response	: 30 Hz - 120 Hz (±3 dB)
Power	: 200 W
Driver Size	: 1 x 250 mm (10 in.)
Dimensions (HxWxD)	: 16.5" x 15.12" x 16.1"
Weight	: 17.12 kg



■ Monitor XT12

12" High Performance, 100W Powered Subwoofer

Low-Pass Crossover Freq	: 80Hz-160/LFE
Peak Power	: 100W
Bass Type	: Bass reflex (ported)
Dimensions (WxHxD)	: 16" x 16.4" x 17.9"
Weight	: 39lbs/17.7kg



■ PSW 10

100W, 10" Front Firing and Front ported Subwoofer

Frequency Response	: 80 Hz - 160 Hz (±3 dB)
Power	: 100 W Peak
Driver Size	: 1 x 250 mm (10 in.)
Dimensions (HxWxD)	: 14.4" x 14.0" x 16.1"
Weight	: 11.8 kg





SURROUND BARS

■ MagniFi MAX AX

FLAGSHIP 5.1.2 DOLBY ATMOS AND DTS:X SOUND BAR WITH 10" WIRELESS SUBWOOFER

NEW



- 11-speaker array with height drivers delivers true Dolby Atmos and DTS:X sound
- Stream music via Wi-Fi (Chromecast, AirPlay 2, Spotify Connect) or Bluetooth
- Experience deep bass you can feel with included 10" wireless subwoofer
- Streamline your setup with 3-in/1-out 4K HDMI switching with eARC
- Dimensions (H x W x D) Main Unit 4.6 in (118 mm), 45 in (1143 mm), 2.8 in (72 mm) 12.85 lb (5.83 kg), Subwoofer : 16 in (407 mm), 1.9 in (302 mm), 15.7 in (399 mm) 26.3 lb (11.9 kg)



■ MagniFi Mini AX

Ultra-Compact Dolby Atmos and DTS:X Sound Bar System

NEW

- Immersive Audio with Dolby Atmos, DTS:X, and Polk SDA 3D Audio Technology
- Stream music via Wi-Fi (Chromecast, AirPlay 2, Spotify Connect) or Bluetooth
- Stream Music via Wi-Fi (Google Chromecast, Apple AirPlay 2, Spotify) or Bluetooth
- Hear Every Word of Dialogue with Patented VoiceAdjust™ and Dedicated Center Channel
- Works with any TV: HDMI, eARC, Optical, AUX, and Roku TV Ready
- Dimensions (H x W x D) : Main Unit 3.1 in (79 mm), 14.4 in (366 mm), 4.1 in (104 mm), Subwoofer : 14.6 in (371 mm), 7.2 in (182 mm), 15.6 in (396 mm)



■ REACT SOUNDBAR

Home Theatre Sound Bar with Alexa Built-In



• Dolby and DTS Support • Movie, music and night modes • (1) HDMI (ARC) output, optical input for TV audio, Bluetooth, (1) USB-A (for firmware updates), Bluetooth" • Unleash true surround sound by adding Polk SR2 wireless rear speakers (sold separately). Push your bass over the top by attaching the wireless Polk React Sub (sold separately) • (2) 96mm x 69mm mid-range drivers, • (2) 25mm tweeters, (2) 110mm x 100mm passive radiators" • Sound Bar: 2.20" H (56mm) x 34.02" W (864mm) x 4.76" D (121mm)



■ REACT SUB

Deep, Impactful Bass for Polk React Series Wireless Sound Bars

Dimensions : "(L)419mm x (W)218mm x (H)348mm
(L)16.5" x (W)8.6" x (H)13.7"
7.5kg / 16.5lbs"

Drivers : (1) 7" Woofer



■ Magnifi MAX SR2

(For Magnifi Mini AX, Max AX, React Bar) Wireless Surround Speakers

Amplifier : 60-watt (peak) or 30 W Each
built-in

Drivers : 1 x 3" Round driver Mid/Woofer

Inputs : Wireless streaming from Magnifi MAX Surround bar

Mounting Type : Horizontal orientation, 1/4 in - 20 Threaded Insert
and Keyhole Hanger.



■ MagniFi 2

High-Performance Home Theatre Sound Bar and Wireless Subwoofer System with Bluetooth & Chromecast Built-in



Total System power : 200 W

Inputs : 3(4K) HDMI In / 1 (ARC) HDMI Out 1 Optical
Wifi & Bluetooth

Driver Size : 4x 1"x3" (25x76 mm) Midrange
2x 0.75" (19 mm) Tweeter

Dimensions : Soundbar : 53 mm, 1092 mm, 96 mm (HxWxD)
Subwoofer : 370 mm, 308 mm, 371 mm (HxWxD)

Weight : Soundbar 2.5 kg, Subwoofer 6.4 kg



■ MagniFi Mini

Home Theatre Sound Bar System



Total System power : 250 W

Inputs : HDMI, Optical, Analog, Bluetooth and WiFi via
GoogleCast

Subwoofer : Wireless 6 1/2" ported, slim

Driver Size : 4 x 2.25" Full range and 2 x 1/2" Tweeters

Dolby Digital Decoding : Dolby Digital 2.0 and 5.1



■ **Signa S3**

Universal TV Soundbar and Wireless Subwoofer System

- System power 150W • Input HDMI ARC, Toslink Optical input for TV audio AUX 3.5 mm, Chromecast built-in and Bluetooth • Driver size (2) 1.25" x 4.4" (32 x 112 mm) full range oval drivers, (2) 1" (25 mm) tweeters • Dimensions Soundbar 898mmWx56mmHx83mmD • Subwoofer 171 mm, Wx311mmxH343mmD • Weight Soundbar 1.5 kg, Subwoofer 4 kg

NEW



■ **Signa S4**

True Dolby Atmos Sound Bar with Wireless Subwoofer, eARC, and Bluetooth

- Signa S4 is Dolby Atmos Certified* to immerse you in 360 degrees of surround sound. • Surround Bar System with wireless subwoofer, 280W, WiFi, Bluetooth, Google Assistant and Chromecast with 4K and 8K TV provides an incredibly realistic sound environment • Plus, standard audio played through the Signa S4 can be up-mixed to create a virtualized Atmos experience.

NEW





**OWM WALL
MOUNT
SPEAKERS**

■ OWM 3
100W, 2-Way 2 Speaker Surround Satellites

Frequency	: 80 Hz-25 kHz
Power Handling	: 100W
Sensitivity	: 89dB
Impedance	: 8 ohms
Driver Size	: 115mm LF/MF, 25 mm HF
Dimensions	: 254 x 178 x 119 mm
Weight	: 2kg





ALL WEATHER SPEAKERS

Polk Audio's award winning Atrium series, designed and built to survive the harshest conditions.

■ Atrium 8 SDI High Performance All Weather Outdoor Loudspeaker with Dual Tweeters and Power Port Bass Venting

Frequency Response	: 45 Hz to 27 kHz
Power (RMS)	: 2 x 125 W
Sensitivity	: 91 dB
Impedance	: 8 ohms
Driver size	: 165 mm LF / MF, 2 x 25 mm HF
Dimension WxHxD	: 216 x 327 x 233 mm
Weight	: 6.12 kg



Also available in white colour

■ Atrium 5 All Weather Outdoor Loudspeaker with 5" Driver and 3/4" Tweeter

Frequency	: 60 Hz -25 kHz
Power(RMS)	: 100 W
Sensitivity	: 90 dB
Impedance	: 8 ohms
Driver size	: 127 mm LF/ MF, 19 mm HF
Dimension(WxHxD)	: 170 x 260 x 196 mm
Weight	: 2 kg



Also available in white colour

■ Atrium 4

All Weather Outdoor Loudspeaker with 4.5" Driver and 3/4" Tweeter

Frequency	: 75 Hz to 25 kHz
Power (RMS)	: 80 W
Sensitivity	: 89 dB
Impedance	: 8 ohms
Driver size	: 114 mm LF/ MF, 19 mm HF
Dimension (WxHxD)	: 144.5 x 219.14 x 169.9 mm
Weight	: 1.63 kg



Also available in white colour

■ ATRIUM SAT300

Compact Staked Outdoor Loudspeaker

Configuration	: 2-way 2-speaker System (Mineral-filled polypropylene cabinet)
Power Handling	: 10 - 100 watts
Driver	: 1 x 0.75" Dynamic Bal polyurethane tweeter, 1 x 3.5" Dynamic Bal mid-range
Sensitivity	: 83 dB SPL
Impedance	: 8 ohms
Overall Frequency Response	: 100Hz - 22Khz (115Hz - 20KHz Lower & Upper -3dB)
Dimensions (H x W x D)	: 177.8 x 139.7 x 213.4 in mm
Weight	: 1.47 kg



■ ATRIUM SUB100

Outdoor Subwoofer with 10-inch Woofer

Configuration	: Acoustic Suspension with Colour-Impregnated Resin Shell
Power Handling	: 10 - 200 W
Driver	: 1 x 10" long-throw dynamic balance composite cone driver with dual voice coils
Sensitivity	: 88dB SPL
Impedance	: 8 ohms
Overall Frequency Response	: 50 Hz - 110 KHz
Dimensions (H x W x D)	: 279.4 x 429.3 x 429.3 mm
Weight	: 7.6 kg





IN-WALL SPEAKERS

■ VS 265-LS

Three Way Bass Reflex Inwall Speaker

Frequency response	: 28 Hz-33 kHz (± 3 dB)
Power	: 10-200W
Sensitivity	: 91dB
Impedance	: 8 ohms
Driver Size	: (1) 1" d (Round) Dynamic Balance ring radiator - Tweeter (2) 6.5" d (Round) Dynamic Balance aerated polypropylene cone and woofer.
Dimensions (HxWxD)	: 20 7/8" x 8 7/8" x 3 3/4"
Weight	: 9 lbs (4.08kg)



■ VS 255C-LS

Two Way Bass Reflex Inwall Speaker

Frequency response	: 30 Hz-33 kHz (± 3 dB)
Power	: 10-150W
Sensitivity	: 90dB
Impedance	: 8 ohms
Driver Size	: (2) 5.25" d (Round) Dynamic Balance aerated polypropylene cone and rubber surround - Mid/Woofer (1) 1" d (Round) Dynamic Balance ring radiator tweeter
Dimensions (HxWxD)	: 9 5/16" x 14 13/16" x 3 3/4"
Weight	: 6.86lbs (3.11kg)



■ VS 265-RT

Three Way Bass Reflex Inwall Speaker

Frequency response	: 30 Hz-27 kHz (± 3 dB)
Power	: 10-200W
Sensitivity	: 91dB
Impedance	: 8 ohms
Driver Size	: (2) 6.5" d (Round) Dynamic Balance mineral composite polypropylene cone with rubber surround - Mid/Woofer (1) 1" d (Round) Dynamic Balance silk/polymer composite dome - Tweeter
Dimensions (HxWxD)	: 20 7/8" x 8 7/8" x 3 3/4"
Weight	: 8.1lbs (3.6Kg)



■ VS 255C-RT

Two Way Bass Reflex Inwall Speaker

Frequency response	: 30 Hz-27 kHz (± 3 dB)
Power	: 10-150W
Sensitivity	: 90dB
Impedance	: 8 ohms
Driver Size	: (2) 5.25" d (Round) Dynamic Balance Mineral Composite Polypropylene Cone with Rubber Surround Mid/Woofer - Mid/Woofer (1) 1" d (Round) Dynamic Balance Silk Polymer Composite Dome Tweeter
Dimensions (HxWxD)	: 9 5/16" x 14 13/16" x 3 3/4"
Weight	: 6.6 lbs (2.99kg)



■ V85

Premium In-wall Speaker

Frequency	: 30 Hz-27 kHz
Power handling	: 10-125W
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-8 & quot; mineral filled polypropylene cone, rubber suspension.
Tweeter	: 1 & quot; soft dome in swivel mount
Dimensions (HxWxD)	: 12 3/4" x 7 1/4 x 3"
Weight	: 2.26kg (4.9 lbs)



■ RC 65i

Premium In-wall Speaker

Frequency	: 32 Hz-27 kHz
Power handling	: 10-125W
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-6.5 & quot; mineral filled polypropylene cone, rubber suspension. Tweeter : 1 & quot; soft dome in swivel mount
Dimensions (HxWxD)	: 14 3/8" x 8 7/8 x 3 1/2"
Weight	: 2.06kg (4.5 lbs)



■ V65

Premium In-wall Speaker

Frequency	: 32 Hz-27 kHz
Power handling	: 10-125W
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-6.5 & quot; mineral filled polypropylene cone, rubber suspension.
Tweeter	: 1 & quot; soft dome in swivel mount
Dimensions (HxWxD)	: 12 3/4" x 7 1/4 x 3"
Weight	: 2.27kg (4.9 lbs)



RC85i
Premium In-wall Speaker

Frequency	: 30 Hz-20 kHz
Power handling	: 20-100W
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-8" mineral filled polypropylene cone, rubber suspension. Tweeter : 1" soft dome in swivel mount
Dimensions (HxWxD)	: 14 1/8" x 10 1/6 x 3"
Weight	: 5.4kg (12 lbs)



RC65i
Premium In-wall Speaker

Frequency	: 50 Hz-20 kHz
Power handling	: 20-100
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-8" mineral filled polypropylene cone, rubber suspension. Tweeter : 1" soft dome in swivel mount
Dimensions (HxWxD)	: 8.6875 x 12.75
Weight	: 5.4kg (12 lbs)



RC55i
Premium In-wall Speaker

Frequency	: 67 Hz-20 kHz
Power handling	: 20-100W
Impedance	: 8 ohms
Sensitivity	: 90dB
Driver Size	: Midrange : 1-5 1/4" mineral filled polypropylene cone, rubber suspension. Tweeter : 3/4" soft dome in swivel mount
Dimensions (HxWxD)	: 11" x 7 9/6 x 2"
Weight	: 3.6kg (8 lbs)





IN-CEILING SPEAKERS

■ VS80F/X LS

High-Performance In-Ceiling Surround Speakers

Frequency Response	: 45 Hz - 29 kHz
Power	: 20-125 W
Sensitivity	: 88 dB (2.83V/ 1m)
Impedance	: 8 ohms
Driver Size	: 8" (20.32 cm) LF 2 x 3/4 (1.91 cm) " HF "cutout: 9-3/8" diameter
Dimensions (HxWxD)	: mounting depth: 5-1/8"



■ VS80F/X RT

High-Performance In-Ceiling Surround Speakers

Frequency Response	: 50 Hz - 25 kHz
Power	: 20-100 W
Sensitivity	: 87 dB (2.83V/ 1m)
Impedance	: 8 ohms
Driver Size	: 8" (20.32 cm) LF 2 x 3/4 (1.91 cm) " HF "cutout: 9-3/8" diameter
Dimensions (HxWxD)	: mounting depth: 4-3/4"



■ V80

Vanishing High-Performance In-Ceiling Speaker

Frequency Response	: 30 Hz - 27 kHz
Power	: 10-100 W
Sensitivity	: 90 dB (2.83V/ 1m)
Impedance	: 8 ohms
Driver Size	: 8" (20.32 cm) LF 1" (2.54 cm) HF
Dimensions (HxWxD)	: "Diameter : 9.375" (23.81 cm) diameter
Depth	: 3.625" (9.21 cm)



■ V60

Vanishing High-Performance In-Ceiling Speaker

Frequency Response	: 33 Hz - 27 kHz
Power	: 10-100 W
Sensitivity	: 89 dB (2.83V/ 1m)
Impedance	: 8 ohms
Driver Size	: 6.5" (16.51 cm) LF 0.75" (1.91 cm) HF
Dimensions (HxWxD)	: "Diameter : 8.188" (20.8 cm) diameter
Depth	: 3.25" (8.26 cm)



■ V60 Slim

Premium In-Ceiling Dolby Atmos Speaker

Frequency response	:	35 Hz-25 kHz
Power	:	10-100W
Sensitivity	:	88dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	(1) 0.75" (1.91 cm) d
(Round) Swivel Mount, Silk	:	Dome - Tweeter
	:	(1) 6.5" (16.51 cm) d (Round) Composite
Polymer Cone with Butyl Rubber	:	
Dimensions	:	8.188" (20.8 cm) diameter
Weight	:	3 kg



■ V6S

Premium In-Ceiling Dolby Atmos Speaker

Frequency response	:	33 Hz-27 kHz
Power	:	10-100W
Sensitivity	:	89dB
Impedance	:	8 ohms (2.8 min.)
Driver Size	:	(1) 0.75" (1.91 cm) (Round) Swivel Mount, Silk
	:	Dome - Tweeter (1) 6.5" (16.51 cm) d (Round)
	:	Composite Polymer Cone with Butyl Rubber
Dimensions	:	8.188" (20.8 cm) diameter
Weight	:	3.5 kg



■ RC80i

Premium In-Ceiling Dolby Atmos Speaker

Frequency	:	35 Hz -20 kHz
Power Handling	:	100 W
Impedance	:	8 ohms
Sensitivity	:	90 dB
Driver Size	:	2 x 165 mm MF
	:	1 X 25 mm HF
Dimensions	:	272 mm Diameter



■ RC60i

Premium In-Ceiling Dolby Atmos speaker

Frequency	:	40 Hz-20 kHz
Power Handling	:	100 W
Impedance	:	8 ohms
Sensitivity	:	89 dB
Driver Size	:	2x165 mm MF
	:	1 X 2 5 mm HF
Dimensions	:	226 mm Diameter



■ RC6S

Premium In-Ceiling Dolby Atmos speaker

Frequency response	:	40 vHz-20 kHz
Power	:	10-100W
Sensitivity	:	89dB
Impedance	:	8 Ohms (2.8 min.)
Driver Size	:	(1) 0.75" (1.91 cm) d (Round) Swivel Mount,
	:	Silk Dome - Tweeter
	:	(1) 6.5" (16.51 cm) d (Round) Composite Polymer
	:	Cone with Butyl Rubber
Cut out Dimensions	:	7.5625" diameter
Weight	:	2.8 kg





Barton Centre, M.G. Road, Bengaluru 560 001, Tel: +91 88843 10123.

Ahmedabad | Bengaluru | Chennai | Coimbatore | Kochi | Hyderabad | Kolkata | Mumbai | Mysuru | New Delhi

*Experience the amazing variety of AV Systems in our exclusive PRO FX showrooms and through our nationwide network of dealers.
If you have a query, write to us: sales@profx.com*

Also, for more information about us, please log on to

www.profx.com

All prices indicated are MRP. All logos and trademarks belong to their respective owners. Specifications and prices are subject to change without prior notice.